

Application Data Sheet

PC-1200 WB Semi-Transparent Stain: All colours

PC-1200 Semi-Transparent Stains are high quality water based wood stains that are fast drying with minimal grain raising. They have a very mild odor and clean-up easily with water.

Uses: Especially formulated for interior and exterior woodwork, wood furniture, cabinets, toys, floors, and more. Use appropriate top coat depending on application. PC-1200 stains can be mixed together at the ratio required to create any desired color stain and/or used a toner to tint PC-77 or PC-88 series top coats

Surface Preparation: The surface should be clean, dry and free from surface contaminants that would prevent proper adhesion such as dust, oil, wax, etc. **Do not use tack cloth, steel wool or oxidized sandpaper.** Do not use over an alkyd stain. Sand surface to 220 grit and remove all dust.

Directions for use:

1. Stir thoroughly before use. Avoid shaking. Strain as necessary.
2. Apply by brush, wipe, or spray. Formulated for best results when sprayed with a HVLP gun or sprayer – use a 1.00mm needle and tip as a starting point. Apply as is – no thinning required.
3. Avoid air bubbles during application. Overlap passes 50% when spraying.
4. One coat should suffice. If applying additional coats, no sanding is required. Remove dust between coats with a clean, damp cloth or air - **DO NOT USE TACK CLOTH.**
5. Can be wiped wet after application or left to dry as is. When wiping, always wipe with the grain.

Drying Time: Dry times will vary depending on temperature, humidity, and whether wiped or not. For best results, apply at temperature between 50-90°F (10-30°C), at relative humidity of 50%. Dry to touch in as little as 20 minutes. Wait 1 hour between coats of stain. Wait 2 hours before applying sealer, pore filler or top coat.

Clean up with warm water. Store in a cool, dry place and keep from freezing. Contact your municipality for waste and container disposal by -laws.

Complimentary Products:

For sealing, use PC-2200 Sanding Sealer.
For a closed pore finish, use PC-1000 Liquid Sprayable Pore Filler.
For top coats, use PC-99 Series Premium Polyurethane, PC-88 Series Polyurethane or PC-77 Series Pre-Catalyzed Varnish.

Technical Information:

Sheen: 6 +/-2?
Solids content by weight: 20 +/-1%
Solids content by volume: 15 +/-1%
VOC content: Maximum 2.46 lbs/Gal (295g/L)

CAUTION: Causes eye irritation on contact. Prolonged or repeated contact may cause skin irritation. Do not take internally. Keep out of the reach of children.

FIRST AID: If swallowed DO NOT INDUCE VOMITTING – seek medical attention immediately. In case of eye contact, flush with water immediately for several minutes and seek medical attention.

WARNING: California Proposition 65 – this product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Always perform tests on samples or on discreet areas before using.
Manufacturer's liability is limited to reimbursement of the purchase price of this product from the original point of purchase.

Manufactured in Canada
Turbinaire Inc.
Dorval, QC (Canada)
1-800-866-4857

For further information, consult
MSDS sheet, or visit web site at
www.turbinaire.com/procoat